




Date	SYM	REVISION RECORD	AUTH	DR.	CK.
08/09/03	A	CHANGED MTL. SPEC. AND ADDED MORE DIM.	T.B.	B.S.	

Ø26.92 [Ø1.06] MAX.



**PCB LAYOUT**



# NOTES:

## 1. MATERIAL:

BODY: FR-NYLON WITH 15% GLASS FILLED, UL94V-0, UL FILE NO. E176060(S)

CONTACT: PHOSPHOR BRONZE, NICKLE PLATED OVERALL WITH SOLDER DIPPED TAILS


APPLICATION FOR 3V LITHIUM BATTERY:

INSULATOR RESISTANCE: 5000M Ω MIN.

OPERATION TEMPERATURE: -55°C TO +105°C

DURABILITY: 50 CYCLES MIN.

CONTACT RESISTANCE: 30M Ω MAX.

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal ±.5 (.020)		Scale	Drawn By B.S. Approved By T.B.
Fractional ± .8 (.030)	Title BATTERY HOLDER FOR CR2450		
Angular ± 3°	Date 08/09/03	Drawing Number BS2450	